



CL5010

**Mortice Latch**

Medium-duty, stainless steel latchbolt head with 'anti-shim' deadlocking plunger, 8mm (5/16") follower. Outside lever turns freely without operating the latchbolt. When a valid code is entered and the Blue LED lights up, the lever will retract the latchbolt. When the door closes the spring latch will automatically lock the door. The key will open the door for management functions. The key may be used to set the lock into Code Free mode so that anyone can open the door without using a code (Classroom Function).



CL5020

**Mortice Lock with Double Cylinder**

Euro profile mortice sash lock with deadbolt and latchbolt safety feature. Outside lever and key functions as CL5010. Lockcase key retracts latchbolt for entry without using a code. Key controls deadbolt position. Deadbolt denies access by code, when projected, safety features allow inside lever handle to retract the deadbolt and latchbolt preventing accidental lock in. The key can be used to open doors for management functions such as security and cleaning.

OPTIONS

**Latch Options:**

2 latch options: 60mm (2 3/8") backset requires 25mm (1") hole, 82mm (3 1/4") deep. 70mm (2 3/4") backset requires 25mm (1") hole, 92mm (3 5/8") deep.

**Audit Trail Kit (P5000AT Kit):**


See CL5010AT for full details.

**Back to Back Option (BB):**

Two coded plates for installation on both sides of the door. Provides coded access in both directions. Internal use only.

**Panic Kit Option (PK):**


Electronic panic access kit to fit with new or existing panic equipment.




For further product model options see price list.

PRODUCT DIMENSIONS

CL5010



CL5020



\*Codelocks electronic locks offer a two year guarantee and will be repaired, serviced or replaced free of charge if they develop a manufacturing fault. Faults caused by misuse, abuse and/or poor fitting are not covered by the guarantees.



**Code Change Method**

Set via keypad using Master Code



**Code Free Mode**

Set via keypad or key

TECHNICAL SPECIFICATIONS

Options	Five available
Operations	200,000 per set of batteries
Batteries	4 x AA Cells CL5010BB 8 x AAA Cells
Low Battery Warning	Red LED will flash on opening to indicate batteries need to be changed
Memory	Stores 80 different User Codes
Spindle Type	8mm (5/16") spring loaded spindle
Material	Zinc Alloy
Door Thickness	35mm – 60mm (1 3/8" – 2 3/8")
Buttons	Individual stainless steel buttons
Non Handed	Locks will fit doors hung on the left or right
Remote Release 1	(Rem 1) option fitted as standard to open lock remotely via cable
Remote Release 2	(Rem 2) option allows connection to alarm release
Fitting Options	Vertical
Finish	PVD (Physical Vapour Deposition) hardwearing low maintenance finishes BS (brushed steel) and PB (polished brass)
Keyed Alike	Supplied Keyed Alike on request
Key Override	As standard
Codes	4, 5 or 6 digit codes giving a maximum of 1,000,000 unique codes
Storeroom Function	Fitted as standard i.e. latch can be retracted by key when turned
Classroom Function	Tailpiece supplied to allow (when fitted) lock to be left in Code Free Mode when key is removed
Standards	Codelocks Fire Kit Packs can be fitted to latch locks for 30 or 60 minute fire doors. Tested in accordance with: BS EN 1634-1:2008 Tested to Grade 2 ANSI A156.2/A156.25 UL/Ulc Fire Rating 3 hours (when fitted with US fire kit)
Suitable for	Internal and external use

